

**FEDERALLY ENFORCEABLE STATE  
OPERATING PERMIT (FESOP)  
OFFICE OF AIR MANAGEMENT**

**Milestone Contractors, L.P.  
4312 Whitelick Drive  
Whitestown, Indiana 46075**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F011-10547-00046	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

<b>SECTION A</b>	<b>SOURCE SUMMARY</b>	<b>5</b>
A.1	General Information [326 IAC 2-8-3(b)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]	
A.4	FESOP Applicability [326 IAC 2-8-2]	
A.5	Prior Permit Conditions	
<b>SECTION B</b>	<b>GENERAL CONDITIONS</b>	<b>8</b>
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-8-1]	
B.3	Permit Term [326 IAC 2-8-4(2)]	
B.4	Enforceability [326 IAC 2-8-6]	
B.5	Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3 (h)]	
B.6	Severability [326 IAC 2-8-4(4)]	
B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.8	Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]	
B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.10	Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]	
B.11	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)]	
B.12	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.13	Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]	
B.14	Emergency Provisions [326 IAC 2-8-12]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination	
B.17	Permit Renewal [326 IAC 2-8-3(h)]	
B.18	Permit Amendment or Modification [326 IAC 2-8-10][326 IAC 2-8-11.1]	
B.19	Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-8-15(b)]	
B.20	Operational Flexibility [326 IAC 2-8-15]	
B.21	Construction Permit Requirement [326 IAC 2]	
B.22	Inspection and Entry [326 IAC 2-8-5(a)(2)]	
B.23	Transfer of Ownership or Operation [326 IAC 2-8-10]	
B.24	Annual Fee Payment [326 IAC 2-8-4(6)] [326 IAC 2-8-16]	
B.25	Advanced Source Modification Approval [326 IAC 2-8-4(11)]	
<b>SECTION C</b>	<b>SOURCE OPERATION CONDITIONS</b>	<b>18</b>
	<b>Emission Limitations and Standards [326 IAC 2-8-4(1)]</b>	
C.1	Overall Source Limit [326 IAC 2-8]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1][IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]	
C.7	Operation of Equipment [326 IAC 2-8-5(a)(4)]	
C.8	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]	
	<b>Testing Requirements [326 IAC 2-8-4(3)]</b>	
C.9	Performance Testing [326 IAC 3-6]	
	<b>Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]</b>	
C.10	Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]	
C.11	Monitoring Methods [326 IAC 3]	
C.12	Pressure Gauge Specifications	

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]**

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]
- C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

- C.17 Monitoring Data Availability
- C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]
- C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)]

**Stratospheric Ozone Protection**

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

**SECTION D.1 FACILITY OPERATION CONDITIONS**

**Aggregate Dryer, Drum Mixer, and Batch Tower ..... 28**

**General Construction Conditions**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.1.4 Particulate Matter (PM) [326 IAC 12][40 CFR 60.90, Subpart I]
- D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]
- D.1.6 General Provisions Relating to NSPS [326 IAC 12-1][40 CFR Part 60, Subpart A]
- D.1.7 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4]
- D.1.8 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1]
- D.1.9 Fuel Oil Usage [326 IAC 2-8-4]
- D.1.10 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

**Compliance Determination Requirements**

- D.1.11 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]
- D.1.12 Sulfur Dioxide Emissions and Sulfur Content

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- D.1.13 Particulate Matter (PM)
- D.1.14 Visible Emissions Notations
- D.1.15 Parametric Monitoring
- D.1.16 Broken or Failed Bag Detection

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

- D.1.17 Record Keeping Requirements
- D.1.18 Reporting Requirements

**SECTION D.2 FACILITY OPERATION CONDITIONS**

**Cold-Mix Asphalt Storage Piles ..... 33**

**General Construction Conditions**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-5-2]
- D.2.5 Cold-Mix (Stockpile Mix) Asphalt Concrete Usage [326 IAC 2-8-4]

**Compliance Determination Requirements**

- D.2.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

D.2.7 Record Keeping Requirements

D.2.8 Reporting Requirements

**SECTION D.3 FACILITY OPERATION CONDITIONS**

**Three (3) Asphalt Storage Tanks and two (2) Fuel Oil Storage Tanks . . . . . 35**

**General Construction Conditions**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

D.3.4 Volatile Organic Compounds (VOC) [326 IAC 12] [40 CFR 60.110b, Subpart Kb]

D.3.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

**Compliance Determination Requirements**

D.3.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

D.3.7 Record Keeping Requirements

**Certification Form . . . . . 37**

**Emergency/Deviation Form . . . . . 38**

**Monthly Report Form . . . . . 40-42**

**Quarterly Compliance Monitoring Report Form . . . . . 43**

## SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-8-3(b)]

---

The Permittee owns and operates a stationary combination batch mix and drum mix hot asphalt plant.

Authorized individual: Ron Terrell  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459  
Indianapolis, Indiana 46242-1459  
Phone Number: 317-788-1040  
SIC Code: 2951  
County Location: Boone  
County Status: Attainment for all criteria pollutants  
Source Status: Federally Enforceable State Operating Permit (FESOP)  
Minor Source, under PSD Rules;

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

---

This stationary source consists of the following emission units and pollution control devices:

- (1) one (1) aggregate dryer capable of processing 450 tons per hour of raw material, equipped with one (1) 115 million (MM) British thermal units (Btu) per hour waste oil-fired burner, using natural gas and No. 2 distillate fuel oil as back-up fuels, with one (1) knockout box and one (1) jet pulse baghouse in series for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1);
- (2) one (1) asphalt drum mixer capable of processing 450 tons per hour of raw material, with a hydro carbon capture system for hydrocarbon emissions control, exhausting to the aggregate dryer, and one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1);
- (3) one (1) batch tower (enclosed portions of the batch plant), processing a maximum of 450 tons per hour of raw material, with fugitive particulate matter emissions from the batch tower controlled by a batch tower fugitive dust capture system which exhausts to the jet pulse baghouse which exhausts at one (1) stack (ID No. S-1). The batch tower consists of the following:
  - (a) one (1) hot elevator;
  - (b) one (1) hot aggregate screen system;
  - (c) five (5) hot aggregate storage bins;
  - (d) one (1) hot aggregate weigh hopper;
  - (e) one (1) 150 gallon hot liquid asphalt weigh bucket; and
  - (f) one (1) pugmill mixer with a maximum hot mix asphalt holding capacity of 12,000 pounds;

- (4) cold-mix (stockpile mix) asphalt storage piles;
- (5) three (3) 22,000 gallon asphalt storage tanks (ID Tank Nos. 22, 23, and 24); and
- (6) two (2) 20,000 gallon fuel oil storage tanks (ID Tank Nos. 25 and 26).

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (1) Propane or liquified petroleum gas, or butane-fired combustion sources with heat input equal to or less than six (6) million Btu per hour:
  - (a) one (1) 0.5 MMBtu per hour propane-fired hand torch used for maintenance purposes.
- (2) Fuel oil-fired combustion sources with heat input equal to or less than two (2) million Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight:
  - (a) one (1) 0.35 MMBtu per hour No. 2 distillate fuel oil fired portable space heater.
- (3) Combustion source flame safety purging on startup.
- (4) The following VOC and HAP storage containers:
  - (a) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.
- (5) Application of oils, greases, lubricants or other nonvolatile materials applied as temporary protective coatings.
- (6) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6 (used for maintenance purposes).
- (7) Closed loop heating and cooling systems.
- (8) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment.
- (9) Paved and unpaved roads and parking lots with public access.
- (10) A laboratory as defined in 326 IAC 2-7-1(21)(C).
- (11) One (1) No. 2 distillate oil-fired hot oil heater, with a maximum rated capacity of 2.2 MMBtu per hour, using natural gas as back-up fuel, exhausting through one (1) stack (ID No. S-2).
- (12) One (1) aggregate cold feed system consisting of:
  - (a) six (6) aggregate feed bins;
  - (b) six (6) feeder conveyors;
  - (c) one (1) collector conveyor;
  - (d) one (1) cold aggregate screen system; and

- (e) one (1) cold aggregate scale conveyor.
- (13) one (1) Reclaimed Asphalt Pavement (RAP) feed system consisting of:
  - (a) one (1) RAP feed bin and one (1) feeder conveyor;
  - (b) one (1) lump breaker system with one (1) access conveyor; and
  - (c) one (1) RAP scale conveyor.
- (14) One (1) hot mix drag slat conveyor with a maximum capacity to transfer 500 tons per hour of hot mix asphalt.
- (15) One (1) hot mix storage system consisting of three (3) hot mix storage silos, each with a maximum storage capacity of 200 tons, with top of silos transfer conveyor systems.
- (16) One (1) dust storage and metering system.
- (17) Aggregate storage piles, with a total maximum storage capacity of 103,470 tons.

**A.4 FESOP Applicability [326 IAC 2-8-2]**

---

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) for a Federally Enforceable State Operating Permit (FESOP).

**A.5 Prior Permit Conditions**

---

- (a) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued.

## **SECTION B GENERAL CONDITIONS**

**B.1 Permit No Defense [IC 13]**

---

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

**B.2 Definitions [326 IAC 2-8-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2, and 326 IAC 2-7 shall prevail.

**B.3 Permit Term [326 IAC 2-8-4(2)]**

---

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

**B.4 Enforceability [326 IAC 2-8-6]**

---

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.

- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

**B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

**B.6 Severability [326 IAC 2-8-4(4)]**

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

**B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]**

---

This permit does not convey any property rights of any sort, or any exclusive privilege.

**B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]**

---

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that IDEM, OAM, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.
- (c) Upon request, the Permittee shall also furnish to IDEM, OAM, copies of records required to be kept by this permit. If the Permittee wishes to assert a claim of confidentiality over any of the furnished records, the Permittee must furnish such records to IDEM, OAM, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, and if the Permittee is making a claim of confidentiality regarding the furnished records, the Permittee must furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

**B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]**

---

IDEM, OAM may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

**B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]**

---

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit constitutes a violation of the Clean Air Act and is grounds for:
- (1) Enforcement action;
  - (2) Permit termination, revocation and reissuance, or modification; and
  - (3) Denial of a permit renewal application.



- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

**B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]**

---

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted under this permit shall contain certification by a authorized individual of truth, accuracy, and completeness. This certification, and any other certification required under this permit, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

**B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]**

---

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015
- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was based on continuous or intermittent data;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
  - (5) Such other facts as specified in Sections D of this permit, IDEM, OAM, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**B.13 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]**

---

(a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each facility:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

**B.14 Emergency Provisions [326 IAC 2-8-12]**

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
  - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Management, Compliance Section) or,  
Telephone No.: 317-233-5674 (ask for Compliance Section)  
Facsimile No.: 317-233-5967

Failure to notify IDEM, OAM, by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
  - (g) Operations may continue during an emergency only if the following conditions are met:
    - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

- (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
  - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
  - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

**B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]**

---

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
  - (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
  - (2) An emergency as defined in 326 IAC 2-7-1(12); or
  - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
  - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination**

[326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- 
- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)]
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM determines any of the following:
- (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAM, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

**B.17 Permit Renewal [326 IAC 2-8-3(h)]**

- 
- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
- (1) A timely renewal application is one that is:
    - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
    - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

- (2) If IDEM, OAM upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]  
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAM takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as needed to process the application.

**B.18 Permit Amendment or Modification [326 IAC 2-8-10] [326 IAC 2-8-11.1]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015  
  
Any such application should be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1) only if a certification is required by the terms of the applicable rule.
- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

**B.19 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-8-15(b)]**

---

The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional condition:

For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.

**B.20 Operational Flexibility [326 IAC 2-8-15]**

---

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:
  - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
  - (2) Any approval required by 326 IAC 2-1 has been obtained;
  - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
  - (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAM, in the notices specified in 326 IAC 2-8-15(b), (c)(1), and (d).

- (b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

- (c) Emission Trades [326 IAC 2-8-15(c)]  
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (d) Alternative Operating Scenarios [326 IAC 2-8-15(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAM or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

**B.21 Construction Permit Requirement [326 IAC 2]**

---

Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997, modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.

**B.22 Inspection and Entry [326 IAC 2-8-5(a)(2)]**

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.  
[326 IAC 2-8-5(a)(4)]
  - (1) The Permittee may assert a claim that, in the opinion of the Permittee, information removed or about to be removed from the source by IDEM, OAM, or an authorized representative, contains information that is confidential under IC 5-14-3-4(a). The claim shall be made in writing before or at the time the information is removed from the source. In the event that a claim of confidentiality is so asserted, neither IDEM, OAM, nor an authorized representative, may disclose the information unless and until IDEM, OAM, makes a determination under 326 IAC 17-1-7 through 326 IAC 17-1-9 that the information is not entitled to confidential treatment and that determination becomes final. [IC 5-14-3-4; IC 13-14-11-3; 326 IAC 17-1-7 through 326 IAC 17-1-9]
  - (2) The Permittee, and IDEM, OAM, acknowledge that the federal law applies to claims of confidentiality made by the Permittee with regard to information removed or about to be removed from the source by U.S. EPA. [40 CFR Part 2, Subpart B]

**B.23 Transfer of Ownership or Operational Control [326 IAC 2-8-10]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).



- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-11(b)(3)]

**B.24 Annual Fee Payment [326 IAC 2-8-4(6)][326 IAC 2-8-16]**

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAM the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee.

**B.25 Advanced Source Modification Approval [326 IAC 2-8-4(11)]**

The requirements to obtain a permit revision under 326 IAC 2-8-11.1 are satisfied by this permit for the proposed emission units, control equipment or insignificant activities in Sections A.2 and A.3 and such modifications occur only during the term of this permit.

**SECTION C SOURCE OPERATION CONDITIONS**

Entire Source
---------------

**Emissions Limitations and Standards [326 IAC 2-8-4(1)]**

**C.1 Overall Source Limit [326 IAC 2-8]**

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
  - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also satisfy the requirements of 326 IAC 2-3 (Emission Offset);
  - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
  - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
- (b) Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)), emissions of particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period.
- (c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided the source's potential to emit does not exceed the above specified limits.
- (d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the plan submitted on January 15, 1999. The plan consists of:

- (a) Fugitive particulate matter emissions from paved roads, unpaved roads, and parking lots shall be controlled by one or more of the following methods:

Paved roads and parking lots:

- (1) power brooming while wet either from rain or application of water on an as needed basis.

Unpaved roads and parking lots:

- (1) paving with asphalt;
- (2) treating with emulsified asphalt on an as needed basis;
- (3) treating with water on an as needed basis;
- (4) double chip and seal the road surface and maintained on an as needed basis.

- (b) Fugitive particulate matter emissions from aggregate stockpiles shall be controlled by one or more of the following methods on an as needed basis:

- (1) maintaining minimum size and number of stock piles of aggregate;
- (2) treating around the stockpile area with emulsified asphalt;
- (3) treating around the stockpile area with water;
- (4) treating the stockpiles with water.

- (c) Fugitive particulate matter emissions from outdoor conveying of aggregates shall be controlled by the following method on an as needed basis:
  - (1) applying water at the feed and the intermediate points.
- (d) Fugitive particulate matter emissions from the transfer of aggregates shall be controlled by one of the following methods:
  - (1) minimize the vehicular distance between transfer points;
  - (2) enclose the transfer points;
  - (3) apply water on transfer points on an as needed basis.
- (e) Fugitive particulate matter emissions from transportation of aggregate by truck, front end loader, etc. shall be controlled by one of the following methods:
  - (1) tarping the aggregate hauling vehicles;
  - (2) maintain vehicle bodies in a condition to prevent leakage;
  - (3) spray the aggregates with water;
  - (4) maintain a 10 MPH speed limit in the yard.
- (f) Fugitive particulate matter emissions from the loading and unloading of aggregate shall be controlled by one of the following methods:
  - (1) reduce free fall distance to a minimum;
  - (2) reduce the rate of discharge of the aggregate;
  - (3) spray the aggregate with water on an as needed basis.

C.7 Operation of Equipment [326 IAC 2-8-5(a)(4)]

All air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.

- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). 326 IAC 14-10-4 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

### **Testing Requirements [326 IAC 2-8-4(3)]**

#### **C.9 Performance Testing [326 IAC 3-6]**

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by the IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

## **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

### **C.10 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]**

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend the compliance schedule an additional ninety (90) days provided the Permittee notify:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule with full justification of the reasons for inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

### **C.11 Monitoring Methods [326 IAC 3]**

Any monitoring or testing performed to meet the applicable requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

### **C.12 Pressure Gauge Specifications**

Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.

## **Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

### **C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

(a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.

(b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within 180 days from the date on which this source commences operation.

The ERP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) If the ERP is disapproved by IDEM, OAM, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.

(d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.

- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAM, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

**C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]**

---

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:
  - (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
  - (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
  - (3) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAM, that the Risk Management Plan is being properly implemented.

All documents submitted pursuant to this condition shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4][326 IAC 2-8-5] [326 IAC 1-6]**

---

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
  - (1) This condition;
  - (2) The Compliance Determination Requirements in Section D of this permit;
  - (3) The Compliance Monitoring Requirements in Section D of this permit;
  - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
  - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
    - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and

- (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
  - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
  - (3) An automatic measurement was taken when the process was not operating; or
  - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]  
[326 IAC 2-8-5]

- 
- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
  - (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

## **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

### **C.17 Monitoring Data Availability**

---

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements in (a) above.

### **C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]**

---

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
  - (1) The date, place, and time of sampling or measurements;
  - (2) The dates analyses were performed;
  - (3) The company or entity performing the analyses;
  - (4) The analytic techniques or methods used;
  - (5) The results of such analyses; and
  - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
  - (1) Copies of all reports required by this permit;



- (2) All original strip chart recordings for continuous monitoring instrumentation;
  - (3) All calibration and maintenance records;
  - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

**C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)]**

---

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Quarterly Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported. The Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period. The reports do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) All instances of deviations as described in Section B- Deviations from Permit Requirements Conditions must be clearly identified in such reports. The Emergency/Deviation Occurrence Report does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

## Stratospheric Ozone Protection

### C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-8-4(10)]

- (1) one (1) aggregate dryer capable of processing 450 tons per hour of raw material, equipped with one (1) 115 million (MM) British thermal units (Btu) per hour waste oil-fired burner, using natural gas and No. 2 distillate fuel oil as back-up fuels, with one (1) knockout box and one (1) jet pulse baghouse in series for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1);
- (2) one (1) asphalt drum mixer capable of processing 450 tons per hour of raw material, with a hydro carbon capture system for hydrocarbon emissions control, exhausting to the aggregate dryer, and one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1); and
- (3) one (1) batch tower (enclosed portions of the batch plant), processing a maximum of 450 tons per hour of raw material, with fugitive particulate matter emissions from the batch tower controlled by a batch tower fugitive dust capture system which exhausts to the jet pulse baghouse which exhausts at one (1) stack (ID No. S-1). The batch tower consists of the following:
  - (a) one (1) hot elevator;
  - (b) one (1) hot aggregate screen system;
  - (c) five (5) hot aggregate storage bins;
  - (d) one (1) hot aggregate weigh hopper;
  - (e) one (1) 150 gallon hot liquid asphalt weigh bucket; and
  - (f) one (1) pugmill mixer with a maximum hot mix asphalt holding capacity of 12,000 pounds.

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 326 IAC 2-8-11.1, WITH CONDITIONS LISTED BELOW.

## Construction Conditions

### General Construction Conditions

- D.1.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

## Effective Date of the Permit

- D.1.2 Pursuant to IC 13-15-5-3, this section of this permit becomes effective upon its issuance.
- D.1.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for revisions pursuant to 326 IAC 2.

## Operation Conditions

### Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.1.4 Particulate Matter (PM) [326 IAC 12] [40 CFR 60.90, Subpart I]

Pursuant to 326 IAC 12, (40 CFR Part 60.90, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the particulate matter emissions from the mixing and drying operations shall be limited to 0.04 grains per dry standard cubic foot (gr/dscf). This is equivalent to a particulate matter emission rate of 19.4 pounds per hour. This limit will also render 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.

D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]

Pursuant to 326 IAC 12, (40 CFR Part 60.92, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the mixing and drying operations shall not discharge or cause the discharge into the atmosphere any gases which exhibit 20% opacity or greater.

D.1.6 General Provisions Relating to NSPS [326 IAC 12-1][40 CFR Part 60, Subpart A]

The provisions of 40 CFR Part 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 60, Subpart I.

D.1.7 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4, particulate matter 10 microns emissions from the aggregate mixing and drying operation shall not exceed 21.98 pounds per hour, including both filterable and condensable fractions. Compliance with this limit will satisfy 326 IAC 2-8-4. Therefore, the Part 70 rules (326 IAC 2-7) do not apply.

D.1.8 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1]

Pursuant to 326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations), sulfur dioxide emissions from the 115.0 million Btu per hour burner for the aggregate dryer shall be limited to:

- (a) 1.6 pounds per MMBtu heat input or a sulfur content of less than or equal to 1.5% when using waste oil; and
- (b) 0.5 pounds per million Btu heat input or a sulfur content of less than or equal to 0.5% when using distillate oil.

D.1.9 Fuel Usage [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4(1), the following limit shall apply:

- (a) the input of waste oil with a maximum sulfur content of 0.75% and waste oil equivalents to the 115.0 MMBtu per hour burner for the aggregate dryer shall be limited to 1,693,061 U.S. gallons per 365 day period, rolled on a daily basis, so that SO<sub>2</sub> emissions are limited below 100 tons per year.
- (b) For purposes of determining compliance, the following shall apply:
  - (1) every MMCF of natural gas burned shall be equivalent to 5.4 gallons of waste oil based on SO<sub>2</sub> emissions, such that the total gallons of waste oil and waste oil equivalent input does not exceed the limit specified; and

- (2) every 1,000 gallons of No. 2 distillate fuel oil burned shall be equivalent to 644.0 gallons of waste oil based on SO<sub>2</sub> emissions and a maximum sulfur content of 0.5 percent such that the total gallons of waste oil and waste oil equivalent input does not exceed the limit specified.

Therefore, the requirements of 326 IAC 2-7 will not apply.

#### D.1.10 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

### **Compliance Determination Requirements**

#### D.1.11 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

During the period no later than 180 days after start-up, the Permittee shall perform PM and PM-10 testing utilizing Methods 5 or 17 (40 CFR 60, Appendix A) for PM and Methods 201 or 201A and 202 (40 CFR 51, Appendix M) for PM-10, or other methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of this valid compliance demonstration. PM-10 includes filterable and condensable PM-10. In addition to these requirements, IDEM may require compliance testing when necessary to determine if the facility is in compliance.

#### D.1.12 Sulfur Dioxide Emissions and Sulfur Content

Compliance shall be determined utilizing one of the following options.

- (a) Pursuant to 326 IAC 3-3-4, the Permittee shall demonstrate that the waste oil sulfur content does not exceed 0.75% by weight and the No. 2 distillate fuel oil sulfur content does not exceed 0.5% by weight by:
  - (1) Providing vendor analysis of fuel delivered, if accompanied by a certification;
  - (2) Analyzing the oil sample to determine the sulfur content of the oil via the procedures in 40 CFR 60, Appendix A, Method 19.
    - (A) Oil samples may be collected from the fuel tank immediately after the fuel tank is filled and before any oil is combusted; and
    - (B) If a partially empty fuel tank is refilled, a new sample and analysis would be required upon filling; or
- (b) Compliance may also be determined by conducting a stack test for sulfur dioxide emissions from the 115.0 MMBtu per hour burner for the aggregate dryer, using 40 CFR 60, Appendix A, Method 6 in accordance with the procedures in 326 IAC 3-2.1.

A determination of noncompliance pursuant to either of the methods specified in (a) or (b) above shall not be refuted by evidence of compliance pursuant to the other method.

#### D.1.13 Particulate Matter (PM)

The baghouse for PM control shall be in operation at all times when the aggregate dryer and mixers are in operation.

### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### D.1.14 Visible Emissions Notations

- (a) Daily visible emission notations of the aggregate dryer baghouse stack exhaust shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

#### D.1.15 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the aggregate mixing and drying operation, at least once daily when the aggregate dryer is in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 1.0 and 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months.

#### D.1.16 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within twelve (12) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within twelve (12) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

### **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

#### D.1.17 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.8 and D.1.9, the Permittee shall maintain records in accordance with (1) through (6) below.
  - (1) Calendar dates covered in the compliance determination period;
  - (2) Actual waste oil and waste oil equivalent usage per day since last compliance determination period and equivalent SO<sub>2</sub> emissions;

- (3) A certification, signed by the owner or operator, that the records of the fuel supplier certifications represent all of the fuel combusted during the period; and

If the fuel supplier certification is used to demonstrate compliance the following, as a minimum, shall be maintained:

- (4) Fuel supplier certifications.
- (5) The name of the fuel supplier; and
- (6) A statement from the fuel supplier that certifies the sulfur content of the fuel oil.

The Permittee shall retain records of all recording/monitoring data and support information for a period of five (5) years, or longer if specified elsewhere in this permit, from the date of the monitoring sample, measurement, or report. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit.

- (b) To document compliance with Condition D.1.14, the Permittee shall maintain records of daily visible emission notations of the aggregate dryer baghouse stack exhaust.
- (c) To document compliance with Condition D.1.15, the Permittee shall maintain the following:
  - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
    - (A) Inlet and outlet differential static pressure.
  - (2) Documentation of all response steps implemented, per event .
  - (3) Operation and preventive maintenance logs, including work purchases orders, shall be maintained.
  - (4) Quality Assurance/Quality Control (QA/QC) procedures.
  - (5) Operator standard operating procedures (SOP).
  - (6) Manufacturer's specifications or its equivalent.
  - (7) Equipment "troubleshooting" contingency plan.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.1.18 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.9 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

## SECTION D.2

## FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]

(4) cold-mix (stockpile mix) asphalt storage piles.

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 326 IAC 2-8-11.1, WITH CONDITIONS LISTED BELOW.

### Construction Conditions

#### General Construction Conditions

D.2.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

#### Effective Date of the Permit

D.2.2 Pursuant to IC 13-15-5-3, this section of this permit becomes effective upon its issuance.

D.2.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for revisions pursuant to 326 IAC 2.

### Operation Conditions

#### Emission Limitations and Standards [326 IAC 2-8-4(1)]

##### D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-5-2]

Pursuant to 326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving), the use of cutback asphalt or asphalt emulsion shall not contain more than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:

- 1) penetrating prime coating
- 2) stockpile storage
- 3) application during the months of November, December, January, February and March.

##### D.2.5 Cold-Mix (Stockpile Mix) VOC Usage [326 IAC 2-8-4]

The VOC usage in the production of cold mix (stockpile mix) asphalt shall be limited to 73.2 tons per 365 consecutive day period, rolled on a daily basis. The total for each day shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous 364 days. This is equivalent to 77.05 tons of diluent used per 365 day period in the production of cold mix (stockpile mix) asphalt based on 95% volatilization. During the first 365 days of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated days of operation shall not exceed 422 pounds per day. Therefore, the requirements of 326 IAC 2-7 will not apply.

#### Compliance Determination Requirements

##### D.2.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the VOC limit specified in Condition D.2.5 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

## **Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

### **D.2.7 Record Keeping Requirements**

- (a) To document compliance with Condition D.2.5, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.2.5.
- (1) diluent used in production of cold mix asphalt per day;
  - (2) amount of diluent used last 365 days;
  - (3) type of liquid binder used; and
  - (4) percent diluent (oil distillate) in liquid binder.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

### **D.2.8 Reporting Requirements**

A quarterly summary of the information to document compliance with Condition D.2.5 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

## **SECTION D.3 FACILITY OPERATION CONDITIONS**

### **Facility Description [326 IAC 2-8-4(10)]**

- (5) three (3) 22,000 gallon asphalt storage tanks (ID Tank Nos. 22, 23, and 24); and
- (6) two (2) 20,000 gallon fuel oil storage tanks (ID Tank Nos. 25 and 26).

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 326 IAC 2-8-11.1, WITH CONDITIONS LISTED BELOW.

### **Construction Conditions**

#### **General Construction Conditions**

- D.3.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

#### **Effective Date of the Permit**

- D.3.2 Pursuant to IC 13-15-5-3, this section of this permit becomes effective upon its issuance.
- D.3.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for revisions pursuant to 326 IAC 2.



## **Emission Limitations and Standards [326 IAC 2-8-4(1)]**

### **D.3.4 Volatile Organic Compounds (VOCs) [326 IAC 12] [40 CFR 60.110b, Subpart Kb]**

---

Pursuant to 40 CFR Part 60.110b, Subpart Kb (Standards of Performance for Volatile Organic Liquid Storage Vessels), the three (3) 22,000 gallon asphalt storage tanks and the two (2) 20,000 gallon fuel oil storage tanks, each with a vapor pressure of less than 15.0 kPa, are subject to 40 CFR Part 60.116b, paragraphs (a), (b), and (d) which require record keeping.

### **D.3.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

## **Compliance Determination Requirements**

### **D.3.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]**

---

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the VOC limit specified in Condition D.3.4 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

## **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

### **D.3.7 Record Keeping Requirements**

---

- (a) To document compliance with Condition D.3.4, the Permittee shall maintain permanent records at the source in accordance with (1) through (3) below:
  - (1) the dimension of each storage vessel;
  - (2) an analysis showing the capacity of each storage vessel; and
  - (3) the true vapor pressure of each VOC stored, indicating that the maximum true vapor pressure of VOC is less than 15.0 kPa for Tanks 22, 23, 24, 25, and 26.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR MANAGEMENT  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
CERTIFICATION**

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- ☐ Annual Compliance Certification Letter
- ☐ Test Result (specify) \_\_\_\_\_
- ☐ Report (specify) \_\_\_\_\_
- ☐ Notification (specify) \_\_\_\_\_
- ☐ Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR MANAGEMENT  
COMPLIANCE DATA SECTION  
P.O. Box 6015  
100 North Senate Avenue  
Indianapolis, Indiana 46206-6015  
Phone: 317-233-5674  
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046

**This form consists of 2 pages**

**Page 1 of 2**

Check either No. 1 or No.2

- ☐ 1. This is an emergency as defined in 326 IAC 2-7-1(12)  
•The Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and  
•The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16
- ☐ 2. This is a deviation, reportable per 326 IAC 2-7-5(3)(c)  
•The Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency/Deviation:

Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation?      Y      N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT COMPLIANCE DATA SECTION

### FESOP Monthly Report (Page 1 of 2)

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046  
Facility: 115 MMBtu/hr burner for the aggregate dryer  
Parameter: Sulfur Dioxide (SO<sub>2</sub>)  
Limit: the input of waste oil with a maximum sulfur content of 0.75% and waste oil equivalents to the 115.0 MMBtu per hour burner for the aggregate dryer shall be limited to 1,693,061 U.S. gallons per 365 day period, rolled on a daily basis. For purposes of determining compliance, every MMCF of natural gas burned shall be equivalent to 5.4 gallons of waste oil based on SO<sub>2</sub> emissions, and every 1,000 gallons of No. 2 distillate fuel oil burned shall be equivalent to 644.0 gallons of waste oil based on SO<sub>2</sub> emissions.

Month: \_\_\_\_\_ Year: \_\_\_\_\_

Day	Fuel Type	Waste Oil and Equivalent Usage This Day (gallons)	Waste Oil and Equivalent Usage Last 364 Days (gallons/day)	365 Day Total Waste Oil and Equivalent Usage (gallons)	Day	Fuel Type	Waste Oil and Equivalent Usage This Day (gallons)	Waste Oil and Equivalent Usage Last 364 Days (gallons/day)	365 Day Total Waste Oil and Equivalent Usage (gallons)
1					17				
2					18				
3					19				
4					20				
5					21				
6					22				
7					23				
8					24				
9					25				
10					26				
11					27				
12					28				
13					29				
14					30				
15					31				
16									

- ☐ No deviation occurred in this month.
- ☐ Deviation/s occurred in this month.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title/Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT COMPLIANCE DATA SECTION

### FESOP Monthly Report (page 2 of 2)

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046  
Facility: 115 MMBtu/hr burner for the aggregate dryer  
Parameter: Sulfur content for fuel oil combustion  
Limit: The maximum sulfur content of the waste oil burned in the 115.0 MMBtu per hour burner for the aggregate dryer shall not exceed 0.75%. The maximum sulfur content of the No. 2 distillate fuel oil burned in the 115.0 MMBtu per hour burner for the aggregate dryer shall not exceed 0.5%.

Month: \_\_\_\_\_ Year: \_\_\_\_\_

Day	Fuel Type	Sulfur Content of Fuel Oils (%)	Heat Content of Fuel Oils (Btu/gal)	Day	Fuel Type	Sulfur Content of Fuel Oils (%)	Heat Content of Fuel Oils (Btu/gal)
1				17			
2				18			
3				19			
4				20			
5				21			
6				22			
7				23			
8				24			
9				25			
10				26			
11				27			
12				28			
13				29			
14				30			
15				31			
16							

- ☐ No deviation occurred in this month.
- ☐ Deviation/s occurred in this month.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR MANAGEMENT COMPLIANCE DATA SECTION

### FESOP Monthly Report

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046  
Facility: cold-mix (stockpile mix) asphalt storage piles  
Parameter: volatile organic compounds (VOC)  
Limit: The VOC usage in the production of cold mix (stockpile mix) asphalt shall be limited to 73.2 tons per 365 consecutive day period, rolled on a daily basis. The total for each day shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous 364 days. This is equivalent to 77.05 tons of diluent used per 365 day period in the production of cold mix (stockpile mix) asphalt based on 95% volatilization. During the first 365 days of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated days of operation shall not exceed 422 pounds per day.

Month: \_\_\_\_\_ Year: \_\_\_\_\_

Day	Diluent Usage This Day (tons)	Diluent Usage Last 364 days (tons)	365 Day Total Diluent Usage (tons)	Day	Diluent Usage This Day (tons)	Diluent Usage Last 364 days (tons)	365 Day Total Diluent Usage (tons)
1				17			
2				18			
3				19			
4				20			
5				21			
6				22			
7				23			
8				24			
9				25			
10				26			
11				27			
12				28			
13				29			
14				30			
15				31			
16							

- ☐ No deviation occurred in this month.
- ☐ Deviation/s occurred in this month.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR MANAGEMENT  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
QUARTERLY COMPLIANCE MONITORING REPORT**

Source Name: Milestone Contractors, L.P.  
Source Address: 4312 Whitelick Drive, Whitestown, Indiana 46075  
Mailing Address: 5950 S. Belmont Avenue, P.O. Box 421459, Indianapolis, Indiana 46242-1459  
FESOP No.: F011-10547-00046

**Months:** \_\_\_\_\_ **to** \_\_\_\_\_ **Year:** \_\_\_\_\_

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted quarterly. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

☐ NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

☐ THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD.

Compliance Monitoring Requirement (eg. Permit Condition D.1.3)	Number of Deviations	Date of each Deviation

Form Completed By: \_\_\_\_\_  
Title/Position: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.



## **Indiana Department of Environmental Management Office of Air Management**

### **Technical Support Document (TSD) for a Federally Enforceable Operating Permit (FESOP)**

#### **Source Background and Description**

**Source Name:** Milestone Contractors, L.P.  
**Source Location:** 4312 Whitelick Drive, Whitestown, Indiana 46075  
**County:** Boone  
**SIC Code:** 2951  
**Operation Permit No.:** F011-10547-00046  
**Permit Reviewer:** Trish Earls/EVP

The Office of Air Management (OAM) has reviewed a FESOP application from Milestone Contractors, L.P. relating to the operation of a stationary combination batch mix and drum mix hot asphalt plant.

#### **Unpermitted Emission Units and Pollution Control Equipment**

There are no unpermitted facilities operating at this source during this review process.

#### **New Emission Units and Pollution Control Equipment Receiving Prior Approval**

The application includes information relating to the prior approval for the construction and operation of the following equipment pursuant to 326 IAC 2-8-4(11):

- (1) one (1) aggregate dryer capable of processing 450 tons per hour of raw material, equipped with one (1) 115 million (MM) British thermal units (Btu) per hour waste oil-fired burner, using natural gas and No. 2 distillate fuel oil as back-up fuels, with one (1) knockout box and one (1) jet pulse baghouse in series for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1);
- (2) one (1) asphalt drum mixer capable of processing 450 tons per hour of raw material, with a hydro carbon capture system for hydrocarbon emissions control, exhausting to the aggregate dryer, and one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S-1);
- (3) one (1) batch tower (enclosed portions of the batch plant), processing a maximum of 450 tons per hour of raw material, with fugitive particulate matter emissions from the batch tower controlled by a batch tower fugitive dust capture system which exhausts to the jet pulse baghouse which exhausts at one (1) stack (ID No. S-1). The batch tower consists of the following:
  - (a) one (1) hot elevator;
  - (b) one (1) hot aggregate screen system;
  - (c) five (5) hot aggregate storage bins;
  - (d) one (1) hot aggregate weigh hopper;

- (e) one (1) 150 gallon hot liquid asphalt weigh bucket; and
  - (f) one (1) pugmill mixer with a maximum hot mix asphalt holding capacity of 12,000 pounds;
- (4) cold-mix (stockpile mix) asphalt storage piles;
- (5) three (3) 22,000 gallon asphalt storage tanks (ID Tank Nos. 22, 23, and 24); and
- (6) two (2) 20,000 gallon fuel oil storage tanks (ID Tank Nos. 25 and 26).

### Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (1) Propane or liquified petroleum gas, or butane-fired combustion sources with heat input equal to or less than six (6) million Btu per hour:
  - (a) one (1) 0.5 MMBtu per hour propane-fired hand torch used for maintenance purposes.
- (2) Fuel oil-fired combustion sources with heat input equal to or less than two (2) million Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight:
  - (a) one (1) 0.35 MMBtu per hour No. 2 distillate fuel oil fired portable space heater.
- (3) Combustion source flame safety purging on startup.
- (4) The following VOC and HAP storage containers:
  - (a) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.
- (5) Application of oils, greases, lubricants or other nonvolatile materials applied as temporary protective coatings.
- (6) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6 (used for maintenance purposes).
- (7) Closed loop heating and cooling systems.
- (8) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment.
- (9) Paved and unpaved roads and parking lots with public access.
- (10) A laboratory as defined in 326 IAC 2-7-1(21)(C).
- (11) One (1) No. 2 distillate oil-fired hot oil heater, with a maximum rated capacity of 2.2 MMBtu per hour, using natural gas as back-up fuel, exhausting through one (1) stack (ID No. S-2).
- (12) One (1) aggregate cold feed system consisting of:
  - (a) six (6) aggregate feed bins;
  - (b) six (6) feeder conveyors;
  - (c) one (1) collector conveyor;
  - (d) one (1) cold aggregate screen system; and

- (e) one (1) cold aggregate scale conveyor.
- (13) one (1) Reclaimed Asphalt Pavement (RAP) feed system consisting of:
  - (a) one (1) RAP feed bin and one (1) feeder conveyor;
  - (b) one (1) lump breaker system with one (1) access conveyor; and
  - (c) one (1) RAP scale conveyor.
- (14) One (1) hot mix drag slat conveyor with a maximum capacity to transfer 500 tons per hour of hot mix asphalt.
- (15) One (1) hot mix storage system consisting of three (3) hot mix storage silos, each with a maximum storage capacity of 200 tons, with top of silos transfer conveyor systems.
- (16) One (1) dust storage and metering system.
- (17) Aggregate storage piles, with a total maximum storage capacity of 103,470 tons.

### Enforcement Issue

There are no enforcement actions pending.

### Recommendation

The staff recommends to the Commissioner that the FESOP be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP application for the purposes of this review was received on January 15, 1999.

### Emission Calculations

See Appendix A of this document for detailed emissions calculations (9 pages).

### Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

Pollutant	Potential To Emit (tons/year)
PM	69,225.6
PM-10	9,059.4
SO <sub>2</sub>	402.3
VOC	66,252.2
CO	43.2
NO <sub>x</sub>	97.6

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential To Emit (tons/year)
Acetaldehyde	less than 10
Arsenic	less than 10
Benzene	less than 10
Cadmium	less than 10
Chromium	less than 10
Cobalt	less than 10
Ethylbenzene	less than 10
Formaldehyde	less than 10
Lead	less than 10
Manganese	less than 10
Nickel	less than 10
Quinone	less than 10
Toluene	less than 10
Total POM	less than 10
Xylene	less than 10
<b>TOTAL</b>	<b>less than 25</b>

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of PM<sub>10</sub>, SO<sub>2</sub>, and VOC are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.

#### Actual Emissions

No previous emission data has been received from the source.

#### Limited Potential to Emit

The table below summarizes the total potential to emit, reflecting all limits, of the significant emission units.

	Limited Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs
Aggregate Drying and Batch or Drum Mixing	84.94	96.30	93.33	25.73	42.31	95.70	22.96
Conveying/Handling*	4.68	2.21	0.0	0.0	0.0	0.0	0.0
Cold Mix Storage	0.0	0.0	0.0	73.20	0.0	0.0	0.0
Storage Piles*	0.74	0.26	0.0	0.0	0.0	0.0	0.0
Insignificant Activities	0.27	0.27	5.67	0.07	0.91	1.93	0.0
<b>Total Emissions</b>	<b>90.63</b>	<b>99.0</b>	<b>99.0</b>	<b>99.0</b>	<b>43.22</b>	<b>97.63</b>	<b>22.96</b>

\* Note: These facilities are also listed as Insignificant Activities.

## County Attainment Status

The source is located in Boone County.

Pollutant	Status
PM-10	attainment
SO <sub>2</sub>	attainment
NO <sub>x</sub>	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO<sub>x</sub>) are precursors for the formation of ozone. Therefore, VOC and NO<sub>x</sub> emissions are considered when evaluating the rule applicability relating to the ozone standards. Boone County has been designated as attainment or unclassifiable for ozone.

## Federal Rule Applicability

- (a) This source is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR 60.90, Subpart I) because it meets the definition of a hot mix asphalt facility pursuant to the rule and it was constructed after June 11, 1973. This rule limits particulate matter emissions to 0.04 grains per dry standard cubic foot (gr/dscf) and also limits visible emissions to 20% opacity. This is equivalent to a particulate matter emission rate of 19.4 pounds per hour. The source will comply with this rule by using a baghouse to limit particulate matter emissions to less than 0.04 gr/dscf (see Appendix A, page 9 of 9, for detailed calculations).
- (b) The three (3) 22,000 gallon asphalt storage tanks (ID Tank Nos. 22, 23, and 24) and the two (2) 20,000 gallon fuel oil storage tanks (ID Tank Nos. 25 and 26) are subject to the requirements of the New Source Performance Standard, 326 IAC 12, (40 CFR 60.110b, Subpart Kb) because the tanks were constructed after July 23, 1984, and each has a storage capacity greater than 40 cubic meters. However, since each tank has a storage capacity greater than 75 cubic meters but less than 151 cubic meters, and the liquid stored in each tank has a maximum true vapor pressure of less than 15.0 kPa, they are not subject to 40 CFR 116b paragraph (c). Also, because the liquid stored in each tank has a maximum true vapor pressure less than 27.6 kPa, they are not subject to the requirements of 40 CFR 60.112b paragraphs (a) or (b). Each tank is subject to only 40 CFR Part 60.116b, paragraphs (a), (b), and (d) which require record keeping.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.

## State Rule Applicability - Entire Source

### 326 IAC 2-6 (Emission Reporting)

This source is not subject to 326 IAC 2-6 (Emission Reporting), which would require the source to submit an annual emission statement. Pursuant to this rule, any physical or operational limitation on the capacity of the source to emit a pollutant, including air pollution equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is enforceable. This source has accepted federally enforceable operation conditions which limit emissions of PM-10, SO<sub>2</sub>, and VOC to below 100 tons per year per pollutant. Also, the source is not one of the twenty-eight (28) listed sources and its potential to emit PM10 is less than one-hundred (100) tons per year including fugitive emissions, therefore, 326 IAC 2-6 does not apply.

326 IAC 2-8-4 (FESOP)

This source is subject to 326 IAC 2-8-4 (FESOP). Pursuant to this rule, the usage of waste oil with a sulfur content of 0.75% and waste oil equivalents in the 115.0 MMBtu per hour burner for the aggregate dryer shall be limited to 1,693,061 U.S. gallons per 365 day period, rolled on a daily basis, so that SO<sub>2</sub> emissions are limited below 100 tons per year. The VOC usage in the production of cold mix (stockpile mix) asphalt shall be limited to 73.2 tons per 365 day period, rolled on a daily basis. This is equivalent to 77.05 tons of diluent used per 365 day period in the production of cold mix (stockpile mix) asphalt based on 95% volatilization. Also, PM-10 emissions from the aggregate dryer shall be limited to 21.98 pounds per hour. The source will comply with the PM-10 emission limit by utilizing a baghouse for controlling PM-10 emissions to 2.4 pounds per hour from the aggregate dryer. Therefore, the requirements of 326 IAC 2-7 do not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

This source is subject to 326 IAC 6-4 for fugitive dust emissions. Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions), fugitive dust shall not be visible crossing the boundary or property line of a source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations)

This source is subject to 326 IAC 6-5 for fugitive particulate matter emissions. Pursuant to 326 IAC 6-5, for any new source which has not received all the necessary preconstruction approvals before December 13, 1985, a fugitive dust control plan must be submitted, reviewed and approved. The fugitive dust control plan for this source includes the following:

- (a) Fugitive particulate matter emissions from paved roads, unpaved roads, and parking lots shall be controlled by one or more of the following methods:

Paved roads and parking lots:

- (1) power brooming while wet either from rain or application of water on an as needed basis.

Unpaved roads and parking lots:

- (1) paving with asphalt;
- (2) treating with emulsified asphalt on an as needed basis;
- (3) treating with water on an as needed basis;
- (4) double chip and seal the road surface and maintained on an as needed basis.

- (b) Fugitive particulate matter emissions from aggregate stockpiles shall be controlled by one or more of the following methods on an as needed basis:

- (1) maintaining minimum size and number of stock piles of aggregate;
- (2) treating around the stockpile area with emulsified asphalt;
- (3) treating around the stockpile area with water;
- (4) treating the stockpiles with water.

- (c) Fugitive particulate matter emissions from outdoor conveying of aggregates shall be controlled by the following method on an as needed basis:
  - (1) applying water at the feed and the intermediate points.
- (d) Fugitive particulate matter emissions from the transfer of aggregates shall be controlled by one of the following methods:
  - (1) minimize the vehicular distance between transfer points;
  - (2) enclose the transfer points;
  - (3) apply water on transfer points on an as needed basis.
- (e) Fugitive particulate matter emissions from transportation of aggregate by truck, front end loader, etc. shall be controlled by one of the following methods:
  - (1) tarping the aggregate hauling vehicles;
  - (2) maintain vehicle bodies in a condition to prevent leakage;
  - (3) spray the aggregates with water;
  - (4) maintain a 10 MPH speed limit in the yard.
- (f) Fugitive particulate matter emissions from the loading and unloading of aggregate shall be controlled by one of the following methods:
  - (1) reduce free fall distance to a minimum;
  - (2) reduce the rate of discharge of the aggregate;
  - (3) spray the aggregate with water on an as needed basis.

#### **State Rule Applicability - Individual Facilities**

##### **326 IAC 6-3-2 (Process Operations)**

The aggregate mixing and drying operation is not subject to the requirements of 326 IAC 6-3-2. This rule does not apply if the limitation established in the rule is not consistent with applicable limitations in 326 IAC 6-1 or 326 IAC 12. Since the applicable PM limit established by 326 IAC 12, 40 CFR 60, Subpart I, is less than the PM limit that would be established by 326 IAC 6-3-2 (67.7 pounds per hour, see Appendix A, page 9 of 9), the more stringent limit applies and the limit pursuant to 326 IAC 6-3-2 does not apply.

##### **326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations)**

The sulfur dioxide emissions from the 115 MMBtu/hr dryer burning waste oil shall be limited to 1.6 pounds per MMBtu heat input. This equates to a fuel oil sulfur content limit of 1.5%. Therefore, the sulfur content of the fuel must be less than or equal to 1.5% in order to comply with this rule (See Appendix A, Page 9 of 9 for detailed calculations). The source will comply with this rule by using waste oil with a sulfur content of 0.75% or less. The sulfur dioxide emissions from the 115 MMBtu/hr dryer burning distillate oil shall be limited to 0.5 lb/MMBtu heat input. This equates to a fuel oil sulfur content limit of 0.5%. Therefore, the sulfur content of the fuel must be less than or equal to 0.5% in order to comply with this rule (See Appendix A, Page 9 of 9 for detailed calculations). The source will comply with this rule by using No. 2 distillate fuel oil with a sulfur content of 0.5% or less.

##### **326 IAC 7-2-1 (Sulfur Dioxide Reporting Requirements)**

This source is subject to 326 IAC 7-2-1 (Reporting Requirements). This rule requires the source to submit to the Office of Air Management upon request records of sulfur content, heat content, fuel consumption, and sulfur dioxide emission rates based on a calendar-month average.

**326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving)**

No person shall cause or allow the use of cutback asphalt or asphalt emulsion containing more than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:

- 1) penetrating prime coating
- 2) stockpile storage
- 3) application during the months of November, December, January, February and March.

This source manufactures stockpile mix for stockpile storage only, therefore, there is no limit on the % of oil distillate in the liquid asphalt used. The source is in compliance with 326 IAC 8-5-2.

**Compliance Requirements**

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

1. The mixing and drying operation has applicable compliance monitoring conditions as specified below:
  - (a) Daily visible emissions notations of the aggregate dryer, drum mixer, and batch tower baghouse stack exhaust shall be performed during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.



- (b) The Permittee shall record the total static pressure drop across the baghouse controlling the aggregate mixing and drying operation, as well as the batch tower, at least once daily when the aggregate dryer is in operation. Unless operated under conditions for which the Preventive Maintenance Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 1.0 to 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

These monitoring conditions are necessary because the baghouse for the mixing and drying operation must operate properly to ensure compliance with 40 CFR Part 60.90 (Subpart I-Standards of Performance for Hot Mix Asphalt Facilities) and 326 IAC 2-8 (FESOP).

### **Air Toxic Emissions**

Indiana presently requests applicants to provide information on emissions of the 188 hazardous air pollutants (HAPs) set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) FESOP Application Form GSD-08.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act Amendments.
- (b) See attached calculations for detailed air toxic calculations. (Appendix A, pages 9 and 10)

### **Conclusion**

The operation of this stationary combination batch mix and drum mix hot asphalt plant shall be subject to the conditions of the attached proposed **(FESOP No.: F011-10547-00046)**.

## **Indiana Department of Environmental Management Office of Air Management**

### **Addendum to the Technical Support Document for Federally Enforceable State Operating Permit (FESOP)**

<b>Source Name:</b>	<b>Milestone Contractors, L.P.</b>
<b>Source Location:</b>	<b>4312 Whitelick Drive, Whitestown, Indiana 46075</b>
<b>SIC Code:</b>	<b>2951</b>
<b>County:</b>	<b>Boone</b>
<b>Operation Permit No.:</b>	<b>F011-10547-00046</b>
<b>Permit Reviewer:</b>	<b>Trish Earls/EVP</b>

On April 8, 1999, the Office of Air Management (OAM) had a notice published in the Lebanon Reporter, Lebanon, Indiana, stating that Milestone Contractors, L.P. had applied for a Federally Enforceable State Operating Permit (FESOP) to operate a stationary combination batch mix and drum mix hot asphalt plant. The notice also stated that OAM proposed to issue a FESOP for this operation and provided information on how the public could review the proposed FESOP and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this FESOP should be issued as proposed.

Upon further review, the OAM has decided to make the following changes to the FESOP:

1. The Construction Conditions listed in section D.4 of the FESOP (conditions D.4.1 through D.4.3) have been moved to the beginning of the D sections for each of the emission units to avoid confusion and to make it easier for the compliance section to prepare its reports after construction is completed. The conditions in sections D.1 through D.3 have been re-numbered accordingly and section D.4 has been removed.

On May 3, 1999, Denis Drysdale submitted comments on behalf of Milestone Contractors, L.P. The summary of the comments and responses is as follows:

#### **Comment #1**

In condition D.1.5(b) of the FESOP, page 29 of 43, please change "equivalent to 712.0 gallons of waste oil" to "equivalent to 644.0 gallons of waste oil", as the original number is based on calculations using the US EPA's AP-42, 5<sup>th</sup> Edition, Section 1.3 - Fuel Oil Combustion, Table 1.3-1 emission factor of 157S for SO<sub>2</sub> for No. 2 oil combustion. This emission factor has now been corrected back to 142S, per the Errata to section 1.3, Fuel Oil Combustion. Also, please correct the potential and limited SO<sub>2</sub> emission calculations in Appendix A, for the aggregate dryer burner to reflect the revised emission factor.

### **Response #1**

Based on the Errata to section 1.3 of AP-42, the SO<sub>2</sub> emission factor for a No. 2 fuel oil fired combustion unit rated at 100 MMBtu per hour or higher has been changed from 157S to 142S, where S represents the sulfur content of the fuel oil. As a result of this, potential SO<sub>2</sub> emissions from the aggregate dryer burner burning No. 2 fuel oil are changed from 282.43 tons per year to 255.45 tons per year (see Appendix A, page 1 of 9). Therefore, the fuel equivalence calculation has been revised such that every 1,000 gallons of No. 2 fuel oil burned shall be equivalent to 644.0 gallons of waste oil (see Appendix A, page 6 of 9). Condition D.1.5, now re-numbered as D.1.9, has been revised to include this as follows (changes in bold or strikeout):

#### **D.1.59 Fuel Usage [326 IAC 2-8-4]**

---

Pursuant to 326 IAC 2-8-4(1), the following limit shall apply:

- (a) the input of waste oil with a maximum sulfur content of 0.75% and waste oil equivalents to the 115.0 MMBtu per hour burner for the aggregate dryer shall be limited to 1,693,061 U.S. gallons per 365 day period, rolled on a daily basis, so that SO<sub>2</sub> emissions are limited below 100 tons per year.
- (b) For purposes of determining compliance, the following shall apply:
  - (1) every MMCF of natural gas burned shall be equivalent to 5.4 gallons of waste oil based on SO<sub>2</sub> emissions, such that the total gallons of waste oil and waste oil equivalent input does not exceed the limit specified; and
  - (2) every 1,000 gallons of No. 2 distillate fuel oil burned shall be equivalent to ~~742.0~~ **644.0** gallons of waste oil based on SO<sub>2</sub> emissions and a maximum sulfur content of 0.5 percent such that the total gallons of waste oil and waste oil equivalent input does not exceed the limit specified.

Therefore, the requirements of 326 IAC 2-7 will not apply.

### **Comment #2**

In condition D.1.12 of the FESOP, page 31 of 43, we would ask that the 8 be changed to 12 which could be a sometime shift, and which IDEM had no problem with in written comments the industry submitted on the model compliance monitoring plan for fabric filter for asphalt plants.

### **Response #2**

On May 3, 1999, Denis Drysdale of Milestone Contractors, L.P. submitted a letter from Ed Stresino of the OAM written on June 17, 1996, to Lloyd Bandy of the asphalt pavement association addressing comments the association made on the model Compliance Monitoring Plan prepared by the OAM. In the letter, Mr. Stresino did not have a problem changing the response time from 8 hours to 12 hours. Therefore, the response time required in the event of baghouse failure in condition D.1.12, now re-numbered as D.1.16, shall be changed from 8 hours to 12 hours. The revised condition now reads as follows (changes in bold or strikeout):

#### **D.1.16 Broken or Failed Bag Detection**

---

In the event that bag failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within ~~eight (8)~~ **twelve (12)** hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within ~~eight (8)~~ **twelve (12)** hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

#### **Comment #3**

In condition D.2.2 of the FESOP, page 33 of 43, we believe the VOC usage should be limited to "72.37 tons". We noticed the form on page 42 of 43 was different from the condition, so when we tried to determine the correct number, we calculated the number listed here. Based on this listed number, the diluent would change to "76.17 tons" and "417 pounds per day", respectively.

#### **Response #3**

The VOC emission limit listed on the report form on page 42 of 43 of the FESOP was found to be incorrect. However, the correct VOC emission limit is as listed in condition D.2.2, now re-numbered as D.2.5. This emission limit is based on a source wide VOC emission limit of 99 tons per year, which includes limited potential VOC emissions of 25.8 tons per year from the aggregate dryer burner, the hot oil heater, and the other insignificant combustion sources. The VOC emissions from the aggregate dryer burner include worst case HAP emissions, which are from a natural gas fired batch mix dryer, and VOC emissions from combustion after the federally enforceable fuel usage limitation is applied. The VOC emission limit calculated by the applicant, listed above, includes the potential VOC emissions from combustion in the aggregate dryer burner, and does not take into account the federally enforceable fuel usage limitation. Therefore, the VOC emission limit as listed in condition D.2.2, now re-numbered as D.2.5, remains unchanged. The report form on page 42 of 43 of the FESOP is now revised to include the correct VOC emission limit.

#### **Comment #4**

In section D.4 of the FESOP, we question if a condition we have seen in prior construction permits needs to be put in there, since this is a new facility. The condition is as follows:

#### **Record Keeping and Reporting Requirements**

##### **D.4. Reporting Requirements**

Pursuant to the New Source Performance Standards (NSPS), Part 60.90, Subpart I, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

1. Commencement of construction date (no later than 30 days after such date);
2. Anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
3. Actual start-up date (within 15 days after such date); and
4. Date of performance testing (at least 30 days prior to such date), when required by a condition elsewhere in this permit.

Reports are to be sent to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P. O. Box 6015

#### **Response #4**

The OAM has recently included a general condition in the model permit to be added to any section D for emission units subject to a New Source Performance Standard (NSPS). This condition states that the general provisions relating to NSPS pursuant to 40 CFR Part 60, Subpart A are applicable to the facility, except when otherwise specified in the applicable NSPS. Therefore, this condition is added as a new condition to section D.1 of the FESOP, numbered as D.1.6. Since the requirements listed in the comment above are cited in 40 CFR Part 60, Subpart A, the new condition D.1.6 will insure that those requirements are complied with. The new condition D.1.6 now reads as follows:

#### **D.1.6 General Provisions Relating to NSPS [326 IAC 12-1][40 CFR Part 60, Subpart A]**

The provisions of 40 CFR Part 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 60, Subpart A.

#### **Comment #5**

In the FESOP Monthly report on page 40 of 43 of the FESOP, please change "equivalent to 712.0 gallons of waste oil" to "equivalent to 644.0 gallons of waste oil", as per the references noted in comment #1 above.

#### **Response #5**

The FESOP Monthly report on page 40 of 43 of the FESOP is revised to show the correct fuel equivalence as stated in response #1 above.

#### **Comment #6**

In the FESOP Monthly report on page 42 of 43 of the FESOP, the VOC usage should be limited to "72.37 tons", the diluent should be limited to "76.17 tons", and "417 pounds per day", as per our calculations noted in comment #3 above. The VOC limit listed in the Limited Potential to Emit table on page 4 of 9 of the TSD, and in the State Rule Applicability section of the TSD, page 6 of 9, pertaining to 326 IAC 2-8-4, should also be changed to 72.37 tons per year

**Response #6**

As stated in response #3 above, the VOC usage limitation for cold mix production as stated in condition D.2.2, now re-numbered as D.2.5, remains unchanged. The report form on page 42 of 43 of the FESOP, which listed an incorrect VOC emission limit, is now revised to include the correct VOC emission limit.

Company Name:	Milestone Contractors, L.P.
Plant Location:	4312 Whitelick Drive, V
County:	Boone
Date Received:	January 15, 1999
Permit Reviewer:	Trish Earls

**\*\* aggregate dryer burner\*\***

The following calculations determine the amount of emissions created by the combustion of waste oil  
 @ 0.75 % sulfur, 1.020 % ash, based on 8,760 hours of use and  
 US EPA's AP-42, 5th Edition, Section 1.11 - Waste Oil Combustion, Tables 1.11-1, 1.11-2, and 1.11-3.

**Criteria Pollutant:** 
$$\frac{115 \text{ MMBtu/hr} * 8760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2000 \text{ lb/ton}} * \text{Ef (lb/1000 gal)} = (\text{ton/yr})$$

<b>P M:</b>	65.3 lb/1000 gal	<b>234.87 ton/yr</b>
<b>P M-10:</b>	52.0 lb/1000 gal	<b>187.16 ton/yr</b>
<b>S O 2:</b>	110.3 lb/1000 gal	<b>396.66 ton/yr</b>
<b>N O x:</b>	19.0 lb/1000 gal	<b>68.36 ton/yr</b>
<b>V O C:</b>	1.0 lb/1000 gal	<b>3.60 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>17.99 ton/yr</b>

The following calculations determine the amount of emissions created by natural gas combustion, from the aggregate dryer burner, based on 8,760 hours of operation and US EPA's AP-42, 5th Edition, Section 1.4 - Natural Gas Combustion, Tables 1.4-1 and 1.4-2.

**Criteria Pollutant:** 
$$\frac{115 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{1000 \text{ Btu/cf} * 2,000 \text{ lb/ton}} * \text{Ef (lb/MMcf)} = (\text{ton/yr})$$

<b>P M:</b>	7.6 lb/MMcf =	<b>3.83 ton/yr</b>
<b>P M-10:</b>	7.6 lb/MMcf =	<b>3.83 ton/yr</b>
<b>S O 2:</b>	0.6 lb/MMcf =	<b>0.30 ton/yr</b>
<b>N O x:</b>	190.0 lb/MMcf =	<b>95.70 ton/yr</b>
<b>V O C:</b>	5.5 lb/MMcf =	<b>2.77 ton/yr</b>
<b>C O:</b>	84.0 lb/MMcf =	<b>42.31 ton/yr</b>

The following calculations determine the amount of emissions created by the combustion of #2 distillate fuel oil  
 @ 0.50 % sulfur, from the aggregate dryer burner, based on 8,760 hours of use and  
 US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Tables 1.3-1, 1.3-2, and 1.3-5.

**Criteria Pollutant:** 
$$\frac{115 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2,000 \text{ lb/ton}} * \text{Ef (lb/1,000 gal)} = (\text{ton/yr})$$

<b>P M:</b>	3.3 lb/1000 gal	<b>11.87 ton/yr</b>
<b>P M-10:</b>	3.3 lb/1000 gal	<b>11.87 ton/yr</b>
<b>S O 2:</b>	71.0 lb/1000 gal	<b>255.45 ton/yr</b>
<b>N O x:</b>	24.0 lb/1000 gal	<b>86.35 ton/yr</b>
<b>V O C:</b>	0.20 lb/1000 gal	<b>0.72 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>17.99 ton/yr</b>

The maximum potential emissions from the aggregate dryer burner due to fuel combustion are the following:

<b>Criteria Pollutant:</b>	<b>Worst Case Fuel</b>
<b>P M:</b> 234.87 ton/yr	Waste Oil
<b>P M-10:</b> 187.16 ton/yr	Waste Oil
<b>S O 2:</b> 396.66 ton/yr	Waste Oil
<b>N O x:</b> 95.70 ton/yr	Natural Gas

**V O C:** 3.60 ton/yr  
**C O:** 42.31 ton/yr

Waste Oil  
Natural Gas

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\*hot oil heater\*\***

The following calculations determine the amount of emissions created by natural gas combustion, from the hot oil heater, based on 8,760 hours of operation and US EPA's AP-42, 5th Edition, Section 1.4 - Natural Gas Combustion, Tables 1.4-1, 1.4-2, and 1.4-3.

**Criteria Pollutant:** 
$$\frac{2.2 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{1000 \text{ Btu/cf} * 2,000 \text{ lb/ton}} * \text{Ef (lb/MMcf)} = (\text{ton/yr})$$

<b>P M:</b>	7.6 lb/MMcf =	<b>0.07 ton/yr</b>
<b>P M-10:</b>	7.6 lb/MMcf =	<b>0.07 ton/yr</b>
<b>S O 2:</b>	0.6 lb/MMcf =	<b>0.01 ton/yr</b>
<b>N O x:</b>	100.0 lb/MMcf =	<b>0.96 ton/yr</b>
<b>V O C:</b>	5.5 lb/MMcf =	<b>0.05 ton/yr</b>
<b>C O:</b>	84.0 lb/MMcf =	<b>0.81 ton/yr</b>

The following calculations determine the amount of emissions created by the combustion of #2 distillate fuel oil @ 0.50 % sulfur, from hot oil heater, based on 8760 hours of use and US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Tables 1.3-1, 1.3-2, and 1.3-6.

**Criteria Pollutant:** 
$$\frac{2.2 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2,000 \text{ lb/ton}} * \text{Ef (lb/1,000 gal)} = (\text{ton/yr})$$

<b>P M:</b>	3.3 lb/1000 gal	<b>0.23 ton/yr</b>
<b>P M-10:</b>	3.3 lb/1000 gal	<b>0.23 ton/yr</b>
<b>S O 2:</b>	71.0 lb/1000 gal	<b>4.89 ton/yr</b>
<b>N O x:</b>	20.0 lb/1000 gal	<b>1.38 ton/yr</b>
<b>V O C:</b>	0.34 lb/1000 gal	<b>0.02 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>0.34 ton/yr</b>

The maximum potential emissions from the hot oil heater due to fuel combustion are the following:

<b>Criteria Pollutant:</b>	<b>Worst Case Fuel</b>
<b>P M:</b> 0.23 ton/yr	Distillate Oil
<b>P M-10:</b> 0.23 ton/yr	Distillate Oil
<b>S O 2:</b> 4.89 ton/yr	Distillate Oil
<b>N O x:</b> 1.38 ton/yr	Distillate Oil
<b>V O C:</b> 0.05 ton/yr	Natural Gas
<b>C O:</b> 0.81 ton/yr	Natural Gas

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\*insignificant combustion sources\*\***

Insignificant combustion units at this source include one (1) propane fired 0.5 MMBtu/hr hand torch, and one (1) No. 2 fuel oil fired 0.35 MMBtu/hr space heater.

The following calculations determine the amount of emissions created by the combustion of #2 distillate fuel oil @ 0.50 % sulfur, based on 8,760 hours of use and US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Tables 1.3-2, 1.3-4, and 1.3-8.

**Criteria Pollutant:** 
$$\frac{0.35 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2,000 \text{ lb/ton}} * \text{Ef (lb/1,000 gal)} = (\text{ton/yr})$$



<b>P M:</b>	3.3 lb/1000 gal	<b>0.04 ton/yr</b>
<b>P M-10:</b>	3.3 lb/1000 gal	<b>0.04 ton/yr</b>
<b>S O 2:</b>	71.0 lb/1000 gal	<b>0.78 ton/yr</b>
<b>N O x:</b>	20.0 lb/1000 gal	<b>0.22 ton/yr</b>
<b>V O C:</b>	0.34 lb/1000 gal	<b>0.00 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>0.05 ton/yr</b>

The following calculations determine the amount of emissions created by propane combustion, based on 8,760 hours of operation and US EPA's AP-42, 5th Edition, Section 1.5 - Liquefied Petroleum Gas Combustion, Table 1.5-1.

$$\text{Criteria Pollutant:} \quad \frac{0.5 \text{ MMBtu/hr} \times 8,760 \text{ hr/yr} \times \text{Ef (lb/1000 gal)}}{91.5 \text{ MMBtu/1000 gal} \times 2,000 \text{ lb/ton}} = (\text{ton/yr})$$

<b>P M:</b>	0.4 lb/1000 gal	<b>0.01 ton/yr</b>
<b>P M-10:</b>	0.4 lb/1000 gal	<b>0.01 ton/yr</b>
<b>S O 2:</b>	0.0 lb/1000 gal	<b>0.00 ton/yr</b>
<b>N O x:</b>	14.0 lb/1000 gal	<b>0.34 ton/yr</b>
<b>V O C:</b>	0.5 lb/1000 gal	<b>0.01 ton/yr</b>
<b>C O:</b>	1.9 lb/1000 gal	<b>0.05 ton/yr</b>

The maximum potential emissions of the insignificant combustion sources are the following:

<b>Criteria Pollutant:</b>	
<b>P M:</b>	<b>0.05 ton/yr</b>
<b>P M-10:</b>	<b>0.05 ton/yr</b>
<b>S O 2:</b>	<b>0.78 ton/yr</b>
<b>N O x:</b>	<b>0.55 ton/yr</b>
<b>V O C:</b>	<b>0.02 ton/yr</b>
<b>C O:</b>	<b>0.10 ton/yr</b>

**\*\* aggregate drying: drum-mix or batch-mix plant \*\***

The following calculations determine the amount of worst case emissions created by aggregate drying before controls, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 11.1 - Hot Mix Asphalt Plants, Table 11.1-2 for a batch mix dryer which has the capability of combusting either fuel oil or natural gas:

(Note: These emissions represent the emissions from a batch mix plant which are higher than those from a drum mix plant)

$$\text{Pollutant:} \quad \frac{\text{Ef} \quad \text{lb/ton} \times \quad 450 \quad \text{ton/hr} \times \quad 8,760 \quad \text{hr/yr}}{2,000 \quad \text{lb/ton}}$$

<b>Criteria Pollutant:</b>	
<b>P M:</b>	35 lb/ton = <b>***** ton/yr</b>
<b>P M-10:</b>	4.5 lb/ton = <b>8,869.50 ton/yr</b>
<b>VOC:</b>	0.011647 lb/ton = <b>22.96 ton/yr</b>

The VOC emission factor for aggregate drying includes l

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\* conveying / handling \*\***

The following calculations determine the amount of emissions created by material handling, based on 8.760 hours of use and AP-42, Section 13.2.4, Equation 1. The emission factor for calculating PM emissions is calculated as follows:

PM-10 Emissions:

$$E = k * (0.0032) * (((U/5)^{1.3}) / ((M/2)^{1.4}))$$

$$= 1.12E-03 \text{ lb PM-10/ton}$$

$$2.37E-03 \text{ lb PM/ton}$$

where k = 0.35 (particle size multiplier for <10um)  
0.74 (particle size multiplier for <30um)

U = 12 mph mean wind speed

M = 4.5 material moisture content (%)

$$\frac{450 \text{ ton/hr} * 8,760 \text{ hrs/yr} * E_f (\text{lb/ton of material})}{2,000 \text{ lb/ton}} = (\text{ton/yr})$$

**Total PM 10 = 2.21 tons/yr**  
**Total PM Emissions = 4.68 tons/yr**

**\*\* storage \*\***

The following calculations determine the amount of emissions created by wind erosion of storage stockpiles, based on 8,760 hours of use and USEPA's AP-42 (Pre 1983 Edition), Section 11.2.3.

Material	Silt Content (wt %)	Pile Size (acres)	Storage Capacity (tons)	PM Emissions tons/yr	PM-10 Emissions tons/yr
Sand	1.2	0.76	19,800	0.19	0.07
Stone	1.1	1.92	50,310	0.45	0.16
Slag	0.9	0.31	8,160	0.06	0.02
RAP	0.2	0.96	25,200	0.04	0.01
<b>Total</b>				<b>0.74</b>	<b>0.26</b>

Sample Calculation:

$$E_f = 1.7 * (s/1.5) * (365-p)/235 * (f/15)$$

$$= 1.39 \text{ lb/acre/day}$$

where s = 1.2 % silt

p = 125 days of rain greater than or equal to 0.01 inches

f = 15 % of wind greater than or equal to 12 mph

$$E_p (\text{storage}) = \frac{E_f * sc * (20 \text{ cuft/ton}) * (365 \text{ day/yr})}{(2,000 \text{ lb/ton}) * (43,560 \text{ sqft/acre}) * (12 \text{ ft})}$$

where sc = 19,800 tons storage capacity

PM = 0.19 tons/yr      P M-10: 35% of PM = 0.07 tons/yr

**\*\* cold mix VOC storage emissions \*\***

The following calculations determine the amount of VOC emissions created by the application of cutback asphalt with a typical value of 35% by volume of diluent, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, §

VOC Emission Factor = 1.7% weight percent flash-off of cold mix

Potential Throughput (tons/yr) = \*\*\*\*\* tons/yr stockpile mix

Potential VOC Emissions (tons/yr) = Potential Throughput (tons/yr) \* wt percent flash-off

**Potential VOC Emissions = 66,225.60 tons/yr**

\* Weight percent flash-off is based on a 7.0 percent by weight of cutback asphalt, containing 35% by volume of diluent of which 95% volatilizes, in stockpile mix and 24% by weight of cutback asphalt evaporated (from Table 4.5-1).

**\*\* summary of source emissions before controls \*\***

Criteria Pollutants:

**P M: 69,225.56 ton/yr**

<b>P M-10:</b>	<b>9,059.41</b>	<b>ton/yr</b>	
<b>S O 2:</b>	<b>402.33</b>	<b>ton/yr</b>	
<b>N O x:</b>	<b>97.63</b>	<b>ton/yr</b>	
<b>V O C:</b>	<b>66,252.22</b>	<b>ton/yr</b>	(VOCs include HAPs from aggregate drying operation)
<b>C O:</b>	<b>43.22</b>	<b>ton/yr</b>	

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\* source emissions after controls \*\***

In order to qualify for the FESOP program, this facility must limit PM-10, SO<sub>2</sub>, and VOC emissions to 99.0 tons per year. Consequently, SO<sub>2</sub> emissions from the aggregate dryer must be limited to 93.33 tons per year (99.0 ton/yr - 5.67 ton/yr from the other combustion sources).

\* Emissions of PM and PM-10 from aggregate drying operations are controlled at 99.880 % control efficiency.

The following calculations determine the amount of emissions created by natural gas combustion based on 1,007 MMcf

**Natural Gas:**  $\frac{\text{***** MMcf/yr}}{2,000 \text{ lb/ton}}$  \* Ef (lb/MMcf) = (ton/yr)

<b>P M:</b>	7.6 lb/MMcf =	<b>4.59E-03 ton/yr *</b>
<b>P M-10:</b>	7.6 lb/MMcf =	<b>4.59E-03 ton/yr *</b>
<b>S O 2:</b>	0.6 lb/MMcf =	<b>0.30 ton/yr</b>
<b>N O x:</b>	190.0 lb/MMcf =	<b>95.70 ton/yr</b>
<b>V O C:</b>	5.5 lb/MMcf =	<b>2.77 ton/yr</b>
<b>C O:</b>	84.0 lb/MMcf =	<b>42.31 ton/yr</b>

The following 0.50 % sulfur

based on 2,629,014 gal/yr:

**No. 2 Distil**  $\frac{\text{***** gal/yr}}{2,000 \text{ lb/ton}}$  \* Ef (lb/1,000 gal) = (ton/yr)

<b>P M:</b>	3.3 lb/1000 gal	<b>5.21E-03 ton/yr *</b>
<b>P M-10:</b>	3.3 lb/1000 gal	<b>5.21E-03 ton/yr *</b>
<b>S O 2:</b>	71.0 lb/1000 gal	<b>93.33 ton/yr</b>
<b>N O x:</b>	24.0 lb/1000 gal	<b>31.55 ton/yr</b>
<b>V O C:</b>	0.20 lb/1000 gal	<b>0.26 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>6.57 ton/yr</b>

The following 0.75 % sulfur

based on 1,693,061 gal/yr:

**Waste Oil**  $\frac{1,693,061 \text{ gal/yr}}{2000 \text{ lb/ton}}$  \* Ef (lb/1000 gal) = (ton/yr)

<b>P M:</b>	65.3 lb/1000 gal	<b>0.07 ton/yr *</b>
<b>P M-10:</b>	52.0 lb/1000 gal	<b>0.05 ton/yr *</b>
<b>S O 2:</b>	110.3 lb/1000 gal	<b>93.33 ton/yr</b>
<b>N O x:</b>	19.0 lb/1000 gal	<b>16.08 ton/yr</b>
<b>V O C:</b>	1.0 lb/1000 gal	<b>0.85 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal	<b>4.23 ton/yr</b>

**Criteria Pollutant:**

<b>P M:</b>	<b>0.07 ton/yr *</b>	<b>Worst Case Fuel</b>
<b>P M-10:</b>	<b>0.05 ton/yr *</b>	Waste Oil
<b>S O 2:</b>	<b>93.33 ton/yr</b>	Waste Oil
		Distillate/Waste Oil

**N O x:** 95.70 ton/yr  
**V O C:** 2.77 ton/yr  
**C O:** 42.31 ton/yr

Natural Gas  
 Natural Gas  
 Natural Gas

Milestone Contractors, L.P.  
 Whitestown, Indiana

Operation F011-10547  
 Plant I D 011-00046

## Primary Fuel Usage Limitations

Fuel Oil: waste oil

$$\frac{93.33 \text{ tons SO}_2/\text{year limited}}{396.66 \text{ tons SO}_2/\text{year potential}} * 7195.71 \frac{\text{Kgals}}{\text{year potential}} = 1693.06 \frac{\text{Kgals}}{\text{year limited}}$$

## Secondary Fuel Usage Limitations

Natural Gas: N/A

Fuel Oil: #2 distillate fuel oil

$$\frac{93.33 \text{ tons SO}_2/\text{year limited}}{255.45 \text{ tons SO}_2/\text{year potential}} * 7195.71 \frac{\text{Kgals}}{\text{year potential}} = 2629.01 \frac{\text{Kgals}}{\text{year limited}}$$

## Primary fuel equivalence limit for natural gas based on SO2 emissions from re-refined waste oil

$$\frac{0.30 \text{ n.g. potential emissions (ton/yr)}}{1007.4 \text{ n.g. potential usage (MMCF/yr)}} / \frac{396.66 \text{ W.O. potential emissions (ton/yr)}}{7195.71 \text{ W.O. potential usage (kgal/yr)}} = 0.0054 \frac{\text{Kgal W.O. burned}}{\text{MMCF n.g. burned}}$$

## Primary fuel equivalence limit for #2 distillate fuel oil based on SO2 emissions from re-refined waste oil

$$\frac{255.45 \text{ #2 F.O. potential emissions (ton/yr)}}{7195.71 \text{ #2 F.O. potential usage (kgal/yr)}} / \frac{396.66 \text{ W.O. potential emissions (ton/yr)}}{7195.71 \text{ W.O. potential usage (kgal/yr)}} = 0.6440 \frac{\text{Kgal W.O. burned}}{\text{Kgal #2 F.O. burned}}$$

**\*\* source emissions after controls \*\***

	misc. combustion:	nonfugitive	
<b>P M:</b>	0.27 ton/yr x	100.00% emitted after controls	<b>0.27 ton/yr</b>
<b>P M-10:</b>	0.27 ton/yr x	100.00% emitted after controls	<b>0.27 ton/yr</b>

	aggregate drying:	nonfugitive	
<b>P M:</b>	68,985.00 ton/yr x	0.12% emitted after controls	<b>82.78 ton/yr</b>
<b>P M-10:</b>	8,869.50 ton/yr x	0.12% emitted after controls	<b>10.64 ton/yr</b>
<b>VOC:</b>	22.96 ton/yr x	100.00% emitted after controls	<b>22.96 ton/yr</b>

	conveying/handling:	fugitive	
<b>P M:</b>	4.68 ton/yr x	50% emitted after controls	<b>2.34 ton/yr</b>
<b>P M-10:</b>	2.21 ton/yr x	50% emitted after controls	<b>1.11 ton/yr</b>

	storage piles:	fugitive	
<b>P M:</b>	0.74 ton/yr x	50% emitted after controls	<b>0.37 ton/yr</b>
<b>P M-10:</b>	0.26 ton/yr x	50% emitted after controls	<b>0.13 ton/yr</b>

cold mix VOC storage: fugitive

## \* \* summary of source emissions after controls \* \*

Criteria Pollutant:	Non-Fugitive	Fugitive	Total
PM:	83.12 ton/yr	2.71 ton/yr	85.83 ton/yr
PM-10:	10.97 ton/yr	1.24 ton/yr	12.21 ton/yr
S O 2:	98.99 ton/yr	0.00 ton/yr	98.99 ton/yr
N O x:	97.63 ton/yr	0.00 ton/yr	97.63 ton/yr
V O C:	25.80 ton/yr	73.20 ton/yr	99.00 ton/yr
C O:	43.22 ton/yr	0.00 ton/yr	43.22 ton/yr

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547

Plant I D 011-00046

## Hazardous Air Pollutants (HAPs)

## \*\* aggregate dryer burner\*\*

The following calculations determine the amount of emissions created by waste oil combustion, from asphalt heating 0.0072 % lead, based on 8,760 hours of use and US EPA's AP-42, 5th Edition, Section 1.11 - Waste Oil Combustion, Tables 1.11-1 and 1.11-4.

Hazardous Air Pollutants (H	115 MMBtu/hr * 8760 hr/yr	* Ef (lb/1000 gal) = (ton/yr)
	140,000 Btu/gal * 2000 lb/ton * 1000 gal/kgal	
	Potential To Emit	Limited Emissions
Lead:	0.396 lb/1000 gal =	1.42 ton/yr
Arsenic:	0.11 lb/1000 gal =	4.75E-04 ton/yr
Cadmium:	0.0093 lb/1000 gal =	4.02E-05 ton/yr
Chromium:	0.02 lb/1000 gal =	8.63E-05 ton/yr
Cobalt:	0.00021 lb/1000 gal =	9.07E-07 ton/yr
Manganese:	0.068 lb/1000 gal =	2.94E-04 ton/yr
Nickel:	0.011 lb/1000 gal =	4.75E-05 ton/yr
	Total HAPs =	2.21 ton/yr
		2.65E-03 ton/yr

Note: The above metallic HAP emission calculations represent the worst case of waste oil, distillate fuel oil, and natural gas combustion.

## \* \* aggregate drying: batch-mix plant \* \*

The following calculations determine the amount of HAP emissions created by aggregate drying before & after controls, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 11.1 - Hot Mix Asphalt Plants, Table 11.1-10 for a batch mix dryer which can be fired with either fuel oil or natural gas. The HAP emission factors represent the worst case emissions (natural gas combustion).

Pollutant:	Ef	lb/ton x	450 ton/hr x	8760 hr/yr
		2000	lb/ton	
Hazardous Air Pollutants (HAPs):			Potential To Emit	Limited Emissions
Acetaldeh	6.40E-04	lb/ton =	1.26 ton/yr	1.26 ton/yr
Benzene:	3.50E-04	lb/ton =	0.69 ton/yr	0.69 ton/yr
Ethylbenz	3.30E-03	lb/ton =	6.50 ton/yr	6.50 ton/yr
Formaladel	8.60E-04	lb/ton =	1.70 ton/yr	1.70 ton/yr
Quinone:	2.70E-04	lb/ton =	0.53 ton/yr	0.53 ton/yr
Toluene:	1.80E-03	lb/ton =	3.55 ton/yr	3.55 ton/yr
**Total Po	1.270E-04	lb/ton =	0.25 ton/yr	0.25 ton/yr
Xylene:	4.30E-03	lb/ton =	8.48 ton/yr	8.48 ton/yr
		Total HAP:	22.96 ton/yr	22.96 ton/yr

\*\* total POM includes 2-Methylnapthalene, Acenaphthene, Acenaphthylene, Anthracene, Benzo(a)anthracene, Benzo(b)fluoranthene, Benzo(k)fluoranthene, Chrysene,

Note: The above organic HAP emission calculations represent the worst case between a drum mix and a batch mix plant.

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\* summary of source HAP emissions potential to emit \*\***

Hazardous Air Pollutants (HAPs):

Acetaldehy	1.261	ton/yr
Arsenic:	0.396	ton/yr
Benzene:	0.690	ton/yr
Cadmium:	0.033	ton/yr
Chromium	0.072	ton/yr
Cobalt:	0.001	ton/yr
Ethylbenze	6.504	ton/yr
Formaldeh	1.695	ton/yr
Lead:	1.425	ton/yr
Manganes	0.245	ton/yr
Nickel:	0.040	ton/yr
Quinone:	0.532	ton/yr
Toluene:	3.548	ton/yr
Total POM	0.250	ton/yr
Xylene:	8.475	ton/yr
<b>Total:</b>	<b>25.167</b>	<b>ton/yr</b>

**\*\* summary of source HAP limited emissions \*\***

Hazardous Air Pollutants (HAPs):

Acetaldehy	1.261	ton/yr
Arsenic:	0.000	ton/yr
Benzene:	0.690	ton/yr
Cadmium:	0.000	ton/yr
Chromium	0.000	ton/yr
Cobalt:	0.000	ton/yr
Ethylbenze	6.504	ton/yr
Formaldeh	1.695	ton/yr
Lead:	0.002	ton/yr
Manganes	0.000	ton/yr
Nickel:	0.000	ton/yr
Quinone:	0.532	ton/yr
Toluene:	3.548	ton/yr
Total POM	0.250	ton/yr
Xylene:	8.475	ton/yr
<b>Total:</b>	<b>22.959</b>	<b>ton/yr</b>

Milestone Contractors, L.P.  
Whitestown, Indiana

Operation F011-10547  
Plant I D 011-00046

**\*\* miscellaneous \*\***

**326 IAC 7 Compliance Calculations:**

The following calculations determine the maximum sulfur content of distillate fuel oil allowable by 326 IAC 7:

$$\begin{array}{rcl} 0.5 \text{ lb/MMBtu} & 140,000 \text{ Btu/gal} = & 70 \text{ lb/1000gal} \\ 70 \text{ lb/1000gal} & 142 \text{ lb/1000 gal} = & 0.5 \% \end{array}$$

Sulfur content must be less than or 0.5% to comply with 326 IAC 7.

The following calculations determine the maximum sulfur content of waste (residual) oil allowable by 326 IAC 7:

$$\begin{array}{rcl} 1.6 \text{ lb/MMBtu} & 140,000 \text{ Btu/gal} = & 224 \text{ lb/1000gal} \\ 224 \text{ lb/1000gal} & 147 \text{ lb/1000 gal} = & 1.5 \% \end{array}$$

Sulfur content must be less than or 1.5% to comply with 326 IAC 7.

### 326 IAC 6-3-2 Compliance Calculations:

The following calculations determine compliance with 326 IAC 6-3-2 for process weight rates in excess of 30 tons per hour:

$$\text{limit} = 55 * ( 450 ^{0.11} ) - 40 = 67.70 \text{ lb/hr or } 296.53 \text{ ton/yr}$$

Since this emission limit exceeds the Subpart I allowable emission limit of 84.94 tons per year, compliance with the PM limit pursuant to 40 CFR 60.90, Subpart I will satisfy the requirements of 326 IAC 6-3-2 and shall render the requirements of 326 IAC 2-2 (PSD) not applicable.

### PM-10 Emission Limit for Aggregate Dryer:

$$\begin{array}{rcl} (99.0 \text{ tons PM-10/yr} - 2.74 \text{ tons PM-10/yr from other sources}) & & \\ = 96.3 \text{ tons PM-10/yr} & = & 21.98 \text{ lbs/hr} \end{array}$$

PM-10 emissions from the aggregate dryer are controlled to less than 21.98 lbs. (Will comply)

### 40 CFR Part 60.90, Subpart I (Standards of Performance for Hot Mix Asphalt Plants) Compliance Calculations:

The following calculations determine compliance with the NSPS, which limits stack emissions from asphalt plants to 0.04 gr/dscf:

$$\frac{82.78 \text{ ton/yr} * 2000 \text{ lb/ton} * 7000 \text{ gr/lb}}{525,600 \text{ min/yr} * 56,563 \text{ dscf/min}} = 0.039 \text{ gr/dscf (will comply)}$$

Allowable p: 84.94 tons per year. 19.39 lbs/hr

Note:

$$\begin{array}{rcl} \text{SCFM} = & 81,326 \text{ acfm} * (460 + 68) * (1 - 0.045) / (460 + 265) \\ = & 56,563 \text{ scfm} \end{array}$$

Assumes exhaust gas temperature of 265F, exhaust gas moisture content of 4.5% and exhaust gas flow of 81,326 acfm.